

PREFABRICATED ACCESSORIES

TPO

PVC

Description

Prefabricated accessories obtained by injection of PVC-P granules and prefabricated accessories obtained by injection of TPO/FPA “Flexible Polypropylene Alloy” granules.

Method of application

- **Angles:** weld the entire surface to the membrane.
- **Fittings for emerging bodies:**
  - weld the whole flange to the membrane;
  - fix the head by means of the fastening collar using Waterstop Mastic and Rubber Sealant.
- **Pipe unions:** weld the membrane on the entire flange.
  - The entire perimeter must be welded, on a width of at least 40 mm.

See RUBBERFUSE Division specifications and instructions.

Standard colours

Angles and fittings for emerging bodies Grey / White


Pipe unions Grey

Spray nozzles Grey

Air vents Black (TPO) / Grey (PVC)

STANDARD ACCESSORIES

DOWNPIPES WITH CUP




Ø 80 shank h. mm 330 with tray  
 Ø 100 shank h. mm 330 with tray  
 Ø 110 shank h. mm 330 with tray  
 Ø 125 shank h. mm 330 with tray  
 Ø 140 shank h. mm 330 with tray  
 Ø 160 shank h. mm 330 with tray  
 Ø 200 shank h. mm 330 without tray

GRAVEL-EXCLUDER / LEAF-EXCLUDER WITH RING




Gravel excluder mesh mm 10 + ring

SINGLE DOWNPIPE



Ø 80 shank h. mm 250 with tray  
 Ø 100 shank h. mm 250 with tray  
 Ø 110 shank h. mm 250 with tray  
 Ø 125 shank h. mm 250 with tray  
 Ø 140 shank h. mm 250 with tray  
 Ø 160 shank h. mm 250 with tray  
 Ø 200 shank h. mm 250 without tray

**CANTILEVERED GRAVEL-LEAF EXCLUDER GRID**





Ø 60-200 gravel-leaf excluder  
Cantilever for Ø 60-200 gravel excluder

**LEAF-EXCLUDER CAGE**




Ø 75-125 leaf excluder cage

**90° ANGULAR DOWNPIPES RECTANGULAR CROSS-SECTION**




Rectangular cross-section mm 65x100 length 500 mm  
Rectangular cross-section mm 100x100 length 500 mm  
Ø 80 elbow 65x100 cross-section  
Ø 100 elbow 65x100 cross-section  
Ø 80 elbow 100x100 cross-section  
Ø 100 elbow 100x100 cross-section  
Leaf/gravel excluder for 65x100 cross-section

**90° ANGULAR DOWNPIPES ROUND CROSS-SECTION**



Round cross-section Ø 80 length 500 mm  
Round cross-section Ø 100 length 500 mm  
Round cross-section Ø 110 length 500 mm  
Round cross-section Ø 125 length 500 mm  
Ø 75 87° elbow  
Ø 110 87° elbow

**AIR VENT**



Ø 75 h 200 mm  
Ø 110 h 325 mm

**PIPING FITTING**




Fitting for pipe Ø 20 to 50 mm  
Fitting for pipe Ø 50 to 90 mm  
Fitting for pipe Ø 75 to 125 mm

**PREFABRICATED ANGLES**



Internal 90°  
External 90°

**RUBBERFUSE PROFILE**



Pyramidal profile made in PVC-P resistant to weather conditions and UV rays.

Rev. 00 (11-15)

As IMPER ITALIA srl has no control over how or where its products are supplied (e.g., over substrates, service conditions, or compliance with instructions), the company cannot accept any liability arising from the use of its product or the results obtained. IMPER ITALIA srl pursues a policy of continuous product improvement. As a result, the company reserves the right to make any necessary changes to the information contained in this publication at any time and without notice.

